



Model Number: D0108D2ULA-22256-F7F7

8-way Dual L-band Active Splitter

With Dual Redundant Amplifiers & LNB Powering



This dual 8-way splitter shelf contains 2 of ETL's 8-way active L-band splitter modules housed in a 2U high, 19" rack mountable shelf. The unit benefits from dual redundant amplifiers and dual redundant power supplies for reliability in service.

Front View of Model D0108D2ULA-22256-F7F7

The unit also provides LNB powering, which can be switched on and off from the rear panel.

Front panel LEDs provide a visual status for the power supplies and amplifier. Monitoring can also be done via a dry contact alarm port on the rear panel.



Rear View of Model D0108D2ULA-22256-F7F7

This particular unit has 70 ohm F-type connectors, but a range of connector types and impedances are available (model numbers will vary).





Model Number: D0108D2ULA-22256-F7F7

8-way Dual L-band Active Splitter with Dual Redundant Amplifiers & LNB Powering

RF Engineering and Custom Build

Technical specifications and operating parameters

RF Parameters		
Capacity	8-way Dual	
Frequency Range	850 – 2150 MHz (L-band)	
Insertion Gain	0 dB ± 2 dB	
Flatness	850-2150MHz	± 2.0 dB
Flatness	Any 36MHz	± 0.5 dB
1dB Compression	0 dBm minimum (at output)	
Noise Figure	12 dB typical	
Amp Redundancy	1-to-1 redundant, cold redundancy & current sensing	
Input Return Loss	10 dB typical	
Output Return Loss	10 dB typical	

System Control	
Display	Front Panel LED's for amplifier & PSU status

Environmental	
Operating temperature	0 to 45°C
Location	Indoor use only
Storage temperature	-20°C to +75°C
Humidity	85% non-condensing

Physical	
Input Connector	F-type
Input Impedance	75Ω
Output Connector	F-type
Output Impedance	75Ω
Dimensions	2U high x 350mm deep x 19" wide
Weight	8 kg
Colour	White 00-E-55 semi-gloss, front panel

Power	
AC Power	85-264V AC, 50/60Hz
LNB Power	18V nominal, 500mA, per channel. Switchable on/off
PSU	Dual redundant
Hot-swap PSU	No

Key Features

One unit containing 2 x 8-way L-band Splitters

Dual redundant power supplies and amplifiers

Front panel LED's for monitoring of the amplifier and splitter status

Switchable LNB Powering

ETL SYSTEMS LIMITED
Coldwell Radio Station
Madley
Hereford
England HR2 9NE

TELEPHONE
+44 (0)1981 259020

EMAIL
info@etlsystems.com

FACSIMILE
+44 (0)1981 259021

WEB
www.etlsystems.com

