



Model Number: **22225-N5N5**

RF Engineering
and Custom Build

Hybrid 8-way L-band Active Splitter & Combiner

With 10MHz Pass



This hybrid unit comprises of an 8-way L-band active splitter and an 8-way L-band active combiner accommodated in a 2U, 19" rack mountable chassis.

Front View of Model 22225-N5N5

The unit provides 10MHz pass from port 1 to the common port for both the splitter and combiner ports, and benefits from dual redundant power supplies which can be monitored via the front panel status LEDs or via a dry contact alarm port on the rear panel.



Rear View of Model 22225-N5N5

This unit has 50 ohm N-type RF connectors, but other impedances and connector types are available (model numbers will vary).





Model Number: 22225-N5N5

RF Engineering
and Custom Build

Hybrid 8-way L-band Active Splitter & Combiner with
10MHz Pass

Technical specifications and operating parameters

RF Parameters		
SPLITTER		
Capacity	8-way	
Frequency Range	850 -2150 MHz (L-band)	
Gain	Gain	-1 dB \pm 1 dB nominal, mean
Amplitude Variations	850-2150MHz	\pm 1.0 dB
	Any 36MHz	\pm 0.5 dB
1dB Compression	0 dBm	
DC Block	Ports 2-8 Blocked	
10 MHz Pass	Port 1 to Common Port	
Input Return Loss	12 dB typical	
Output Return Loss	15 dB typical	
COMBINER		
Capacity	8-way	
Frequency Range	850-2150 MHz (L-band)	
Gain	-1 dB \pm 1 dB nominal, mean	
Amplitude Variations	850-2150MHz	\pm 1.0 dB
	Any 36MHz	\pm 0.5 dB
1dB Compression	+10 dBm	
DC Block	Ports 2-8 Blocked	
10MHz Pass	Port 1 to Common Port	
Input Return Loss	15 dB typical	
Output Return Loss	15 dB typical	

Environmental	
Operating temperature	0 to 45°C
Location	Indoor use only
Storage temperature	-20°C to +75°C
Humidity	85% non-condensing

Physical	
Connectors	N-type
Impedance	50Ω
Dimensions	2U high x 350mm deep x 19" wide
Weight	8 kg
Colour	White 00-E-55 semi-gloss

Power	
AC Power	85-264Vac 50/60Hz
LNB Power	None
PSU	Dual redundant
Hot-swap PSU	No

System Control	
Display	Front Panel LED's for Power & PSU
Alarms	Dry contact alarm port on rear

Key Features	
Hybrid unit containing 1 x 8-way Splitter & 1 x 8-way	
10MHz Pass	
Dual redundant power supplies	

ETL SYSTEMS LIMITED
Coldwell Radio Station
Madley
Hereford
England HR2 9NE

TELEPHONE
+44 (0)1981 259020
EMAIL
info@etlsystems.com

FACSIMILE
+44 (0)1981 259021
WEB
www.etlsystems.com

