



Model Number: **D0104Q1ULA-F7F7-XPSU**

4-way Quad L-band Active Splitter

Powered by an external Power Supply



Front view of Model D0104Q1ULA-F7F7-XPSU

This shelf contains 4 of ETL's 4-way L-band active equalised splitter modules housed in a 1U shelf. It is powered by an external DC supply.

This external power supply system makes economic sense if 3 or more splitter shelves are in use (compared to an integral PSU system).



Rear view of a Model D0104Q1ULA-B5B5-XPSU (with 50 ohm BNC connectors)

This particular unit is supplied with 75 ohm BNC connectors, but a range of impedances and connector types are available (model numbers will vary).





Model Number: D0104Q1ULA-F7F7-XPSU

4-Way Quad L-band Active Splitter powered by an external Power Supply

Technical specifications and operating parameters

RF Parameters	
Capacity	4- way (quad)
Frequency Range	850-2150 MHz (L-band)
Gain	4 dB \pm 1 dB
Flatness	1.5 dB
1dB Compression	0 dBm
Noise Figure	7 dB
Input Return Loss	10 dB typical
Output Return Loss	12 dB typical

System Control	
Display	Front Panel LED for Power status

Environmental	
Operating temperature	0 to 45°C
Location	Indoor use only
Storage temperature	-20°C to +75°C
Humidity	85% non-condensing

Physical	
Input Connector	F-type
Input Impedance	75 Ω
Output Connector	F-type
Output Impedance	75 Ω
Dimensions	1U high x 350mm deep x 19" wide
Colour	White 00-E-55 semi-gloss, front panel

Power	
DC Power	External DC supply required (18V and 50 mA per splitter)
LNB Power	None
PSU	N/A
Hot-swap PSU	N/A

Key Features	
4-way quad splitter in a compact 1U high shelf	
External power supply	
Front Panel LED for Power status	

