



Model Number: **D0108D2ULA-F7F7-D8**

8-way Dual L-band Active Splitter

With switchable LNB Powering



This splitter shelf contains 2 of ETL's 8-way active L-band splitter modules housed in a 2U high, 19" rack mountable shelf. The unit benefits from dual redundant power supplies and switchable LNB Powering (the LNB bias for each RF input port can be switched on and off from the rear panel).

Front View of Model D0108D2ULA-F7F7-D8

Front panel LEDs provide a visual status for the power supplies, and monitoring can also be done via a dry contact alarm port on the rear panel.



Rear View of Model D0108D2ULA-F7F7-D8

This particular unit has 75 ohm F- type connectors, although it is available in a variety of impedances and connector types (model numbers will vary).





Model Number: D0108D2ULA-F7F7-D8

8-way Dual L-band Active Splitter with switchable LNB Powering

RF Engineering and Custom Build

Technical specifications and operating parameters

RF Parameters		
Capacity	8-way Dual	
Frequency Range	850 – 2150 MHz (L-band)	
Insertion Gain	0 dB \pm 2 dB nominal, mean across band	
Flatness	850-2150MHz	\pm 2.0 dB
	Any 36MHz	\pm 0.5 dB
1dB Compression	0 dBm	
Input Return Loss	10 dB typical	
Output Return Loss	10 dB typical	

Physical	
Input Connector	F-type
Input Impedance	75 Ω
Output Connector	F-type
Output Impedance	75 Ω
Dimensions	2U high x 350mm deep x 19" wide
Weight	8 kg
Colour	White 00-E-55 semi-gloss (front panel)

System Control	
Display	Front panel LED's for PSU & Amplifier status
Alarms	Dry contact alarm port on ear panel for PSU failure

Power	
AC Power	85-264V AC (50/60Hz) Fused 2A
LNB Power	18V DC nominal 500mA per channel, switchable on/off at
PSU	Dual redundant
Hot-swap PSU	No

Environmental	
Operating temperature	0 to 45°C
Location	Indoor use only
Storage temperature	-20°C to +75°C
Humidity	85% non-condensing

Key Features	
Dual redundant power supplies	
Front panel LEDs for PSU monitoring	
Dry contact alarm port for PSU failure	

ETL SYSTEMS LIMITED
Coldwell Radio Station
Madley
Hereford
England HR2 9NE

TELEPHONE
+44 (0)1981 259020
EMAIL
info@etlsystems.com

FACSIMILE
+44 (0)1981 259021
WEB
www.etlsystems.com

