



Model Number: 2745A-F7F7

RF Engineering
and Custom Build

16 Port LNB Power Supply Unit

With current monitoring (via RS232 serial port)




Front View of Model 2745A-F7F7

This power supply unit is designed to supply DC injection for up to 16 LNB's, via individual DC inject modules on the rear panel which provide a fused supply at 500mA, 18V nominal.

Loop through connections are provided to allow connection to the LNBs on the top row of connections and provide a DC blocked output on the lower row.

The unit benefits from dual redundant hot-swap power supplies for reliability in service. Front panel LED's provide a visual status of the power supplies and operation of the 16 individual LNB current feeds. A dry contact alarm port is supplied for external current monitoring.



Rear View of Model 2745A with 75 ohm BNC connectors

This unit is supplied with 75 ohm F-type connectors, but a range of connector types and impedances are available (model numbers will vary).





Model Number: 2745A-F7F7

RF Engineering
and Custom Build

16 Port LNB Power Supply Unit with current monitoring (via RS232 serial port)

Technical specifications and operating parameters

RF Parameters	
Capacity	16 individual DC inject modules (for up to 16 LNB's)
Frequency Range	850-2150 MHz (L-band)
Insertion Loss	1 dB nominal
Flatness	850-2150MHz ± 0.75 dB
Input Return Loss	10 dB typical
Output Return Loss	10 dB typical
System Control	
Display	Front panel LEDs for PSU & LNB Supply status
Alarms	Dry Contact Alarm Port on rear panel for current monitoring
Environmental	
Operating temperature	0 to 45°C
Location	Indoor use only
Storage temperature	-20°C to +75°C
Humidity	85% non-condensing
Physical	
Input Connector	F-type
Input Impedance	75Ω
Output Connector	F-type
Output Impedance	75Ω
Dimensions	3U high x 350mm deep x 19" wide
Weight	12kg
Colour	White 00-E-55 semi-gloss (Front panel)
Power	
AC Power	85-264V AC (50/60Hz) Fused 2A
LNB Power	18V nominal, 500mA max per channel
PSU	Dual redundant
Hot-swap PSU	Yes
Key Features	
Hot-swap PSU modules	
Dry contact alarm port for current monitoring and PSU failure	
LEDs for PSU monitoring	

ETL SYSTEMS LIMITED
Coldwell Radio Station
Madley
Hereford
England HR2 9NE

TELEPHONE
+44 (0)1981 259020
EMAIL
info@etlsystems.com

FACSIMILE
+44 (0)1981 259021
WEB
www.etlsystems.com

