

850-2150 MHz

Model Number:


DIV08L1A-2398

10MHz and DC pass from common port to port-1. All other ports are DC & 10MHz blocked

- Current flow is restricted in one direction, into the common port only
- Unity gain
- There is a separate DC inject port to facilitate LNB bias

Available with RF connector options:

- 50 Ω SMA
- 50 Ω N-type
- 50 Ω BNC
- 75 Ω BNC
- 75 Ω F-type





10MHz Reject

ŔF

DC Block

10MHz Pass

RF DC Pass (one way)

> Compact Housed in rugged compact enclosure

> > **Flexible Mounting**

Tapped screw & through hole mounting options

RF Parameters						
DIV08L1A-2398-XXXX		S5S5	N5N5	B5B5	B7B7	F7F7
Frequency Range		850-2150 MHz				
RF Connectors		50Ω SMA	50Ω N-Type	50Ω BNC	75Ω BNC	75Ω F-Type
Mean Gain (dB)		0±1.5	0±1.5	0±1.8	0±2.0	0±2.5
Flatness ± (dB)		1.0	1.0	1.0	1.2	1.5
Input Return Loss (dB)	Тур.	14	12	12	12	10
	Min	8	8	8	8	8
Output Return Loss (dB)	Тур.	16	15	15	12	12
	Min	12	12	10	10	8
Output P1dB GCP** (dBm)	Тур.	1	1	1	1	1
	Min	-2	-2	-2	-2	-2
Isolation (dB)	Тур.	16	16	16	16	16
Output IP3 (dBm)	Тур.	10	10	10	10	10
Noise Figure (dB)	Тур.	8	8	8	8	8
10MHz Insertion Loss is 0 ±3dB*						

Broadcast

*To ports which are applicable **GCP (Gain Compression Point)



Marine Oil & Gas

8-way L-band Active Splitter

DIV08L1A-2398

10MHz Pass

RF

DC Pass (one way

9-26V



SNG & VSAT



Satellite Teleport



www.etlsystems.com



Operating Temperature
Storage Temperature

Location


Humidity


Altitude

Model Number: DIV08L1A-2398

8-way L-band Active Splitter

Technical specifications and operating parameters





vironmental					
	0°C to +45°C				
	-20°C to +75°C				

Indoor use Only 85% non-condensing

10,000 feet

Max


Max

Max Operating Parameters				
Input RF Power	+16 dBm (40mW)			
DC Voltage	35V on any RF port			
DC Current Max	500mA			
DC Consumption	100mA Max, 80mA typical			

Operation beyond these limits may cause instantaneous and permanent damage.

4x M3 | HRU ALL

Physical Dimensions (mm)



Note: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved specification accuracy.

ETL SYSTEMS LIMITED Coldwell Radio Station Madley Hereford England HR2 9NE

TELEPHONE +44 (0)1981 259020

EMAIL info@etlsystems.com

FACSIMILE +44 (0)1981 259021

WEB www.etlsystems.com









