


Model Number: **TEEL1-4006**

RF Components

L-Band Bias Tee

850 - 2150 MHz



500mA current rating

Available with RF connector options:

- 50 Ω SMA
- 50 Ω N-type
- 50 Ω BNC
- 75 Ω BNC
- 75 Ω F-type.



RF Parameters							
TEEL1-4006-XXXX		S5S5	N5N5	B5B5	B7B7	F7F7	
Frequency Range		850 - 2150 MHz					
RF Connectors		50Ω SMA	50Ω N-Type	50Ω BNC	75Ω BNC	75Ω F-Type	
Mean Insertion Loss (dB)		0.3±0.3	0.3±0.3	0.3±0.3	0.5±0.3	0.5±0.3	
Flatness ± (dB)		0.3	0.3	0.3	0.5	0.5	
Input Return Loss (dB)	Тур.	18	18	18	18	18	
	Min	12	12	12	12	12	
Output Return Loss (dB)	Тур.	18	18	18	18	18	
	Min	12	12	12	12	12	
10MHz Insertion loss is ± 3dB* *To ports which are applicable							

Broadcast









Model Number: **TEEL1-4006**


L-Band Bias Tee

Technical specifications and operating parameters


Environmental				
Operating Temperature	0°C to 45°C			
Storage Temperature	-20°C to +75°C			
Location	Indoor use Only			
Humidity	85% non-condensing			
Altitude	10,000 feet			

Max Operating Parameters					
Input RF Power	+37 dBm (5W)				
DC Voltage	28V on any RF port				
DC Current	0.5A				

Operation beyond these limits may cause instantaneous and permanent damage.








Return Loss (dB)

Physical Dimensions



Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy. Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.

ETL SYSTEMS LIMITED Coldwell Radio Station Madley Hereford England HR2 9NE TELEPHONE +44 (0)1981 259020 FACSIMILE +44 (0)1981 259021

EMAIL info@etlsystems.com

WEB www.etlsystems.com



Model Number: **TEEL1-4006**

L-Band Bias Tee

DC Connector Options

We are able to offer the following options for connecting external DC power supplies:

Option 1

As standard our units are supplied with a feed-thru port for external soldering of power supply cable.

Option 2

For a Male Molex DC connector supplied on the Bias TEE please use the model number and add "/1" eg. TEEL1-4007-N5N5/1

Option 3

For a Female Molex socket and cable assembly please use the model number: CABMLX-1500-F or refer to the ETL accessories section on our website.





External Power Supplies

PSU Range							
Model Number	Input	Output	Other				
PSU12F125-9701-SLP	100-240V (AC), 0.6A	12V (DC), 1.25A	Solder pin output				
PSU12F125-9701-ML2	100-240V (AC), 0.6A	12V (DC), 1.25A	Female 3 pin Molex socket				
PSU48F150-9703-SLP	100-240V (AC), 2.5A	48V (DC), 3.13A	Solder pin output				
PSU48F150-9703-ML2	100-240V (AC), 2.5A	48V (DC), 3.13A	Female 3 pin Molex socket				
Pricing available on request							

PSU12F125-9701









