

## Model Number: C1601S2UIA-B5N5

# 16-way Single IF Active Combiner



This single 16-way active IF combiner operates over a frequency range of 20-200 MHz and is housed in a 2U high shelf.

#### Front View of Model C1601S2UIA-B5N5

This unit benefits from dual redundant power supplies for reliability in service, which can be monitored via front panel LEDS and via a dry contact alarm port on the rear panel.



Rear View of Model C1601S2UIA-B5N5

This particular unit is supplied with 50 ohm BNC connectors (IN) and 50 ohm N-type connectors (OUT), but is available in a variety of impedances and connector types (model numbers will vary).

















## Model Number: C1601S2UIA-B5N5

RF Engineering and Custom Build

16-way Single IF Active Combiner

### Technical specifications and operating parameters

RF Parameters				
Capacity		16- way		
Frequency Range		20-200 MHz (IF)		
Gain		0 dB ± 1 dB nominal, mean across band		
Flatness	Over 20-200MHz	± 0.5 dB	± 0.4 dB typical	
	Any 36MHz	± 0.25 dB	± 0.2 dB typical	
1dB Compression		+10 dBm		
Noise Figure		20 dB		
Input Return Loss		18 dB	20 dB typical	
Output Return Loss		18 dB	20 dB typical	

	System Control
Display	Front Panel LED's for Power & PSU status
Alarms	Dry contact alarm port on rear panel for PSU failure

Environmental		
Operating temperature	0 to 45°C	
Location	Indoor use only	
Storage temperature	-20°C to +75°C	
Humidity	85% non-condensing	

Physical		
Input Connectors	BNC	
Input Impedance	50Ω	
Output Connectors	N-type	
Output Impedance	50Ω	
Dimensions	2U high x 350mm deep x 19" wide	
Weight	8 kg	
Colour	White 00-E-55 semi-gloss (Front panel)	

Power		
AC Power	85-264V AC (50/60Hz), Fused 2A	
LNB Power	None	
PSU	Dual Redundant	
Hot-swap PSU	No	

<b>Key Feat</b>	ur	es
-----------------	----	----

Dual redundant power supplies

Front Panel LED's for power & PSU status

Dry contact alarm port on rear panel for PSU failure

ETL SYSTEMS LIMITED Coldwell Radio Station Madley Hereford England HR2 9NE TELEPHONE +44 (0)1981 259020

981 259020

info@etlsystems.com

FACSIMILE +44 (0)1981 259021

WEB www.etlsystems.com







