

1200-1500W C-Band BUC / SSPA

Super High Power Density

Smaller, lighter and more powerful, this series allows significant high-power BUC / SSPA size and weight reduction and at the same time substantially improves thermal efficiency, which leads to higher reliability and longer MTBF.

The 1200W-1500W C-Band powered by GaN technology KiloBUC® series are compact, lightweight and extremely powerful. Weighing 55KG at 1.5KW output power, this new C-band product family is the most powerful and feature rich for its size.

This series features best in class RF characteristics, RF sample port, true RMS power measurements, extensive monitor and control capabilities enabled via Ethernet, Serial and/or Analog Interfaces. The remarkably compact size and high thermal efficiency results in overall system size and cost reduction

Options

- Internal 10MHz Reference clock
- Automatic Level Control (ALC)
- Antenna Mounting Kit
- 1:1 and 1:2 Redundancy Kit
- Remote Control Panel



Features

- Extremely High Power Density
- o Up to 1.5KW Psat in 61 x 51 x 32 cms
 - Superior RF performance
- o Superior Phase Noise: 8 dB better than IESS308/309 recommendation
- o Spurious emission below -60 dBc
- o Wide range Gain Control
- o Highest Linearity at small back-off
 - RF Overdrive Protection
 - Redundancy ready with no external controller required
 - Status LED
 - Analogue Interface
- Available in different frequency options
 - o Super-extended 5.85-6.725GHz
 - o Palapa 6.425-6.725GHz
 - o Insat 6.725-7.025GHz
 - Extensive M&C capability
 - o Serial: RS 232 & RS 485
 - o Ethernet: embedded Web browser (HTTP) & SNMPv3 support
 - Input and output True RMS power detection
 - Field upgradable software



RF Parameters		
Output Frequency Band, GHz	5.85-6.425GHz (other options available)	
Input L Band Frequencies, MHz	950-1525MHz	
Conversion Gain, dB	80 minimum	
Gain Flatness, dB	+/-1 typical +/-1.5 maximum over full band +/-0.4 maximum over any 40MHz	
Gain Stability, dB	+/-1.5 maximum over full temperature range	
Gain Control, dB	20dB minimum dynamic range	
Linearity at Pout=Plin:	2 tone IMD	-25dBc max
	Spectral Regrowth	-30dBc for QPSK at 1 x symbol rate
Input Impedance, Ohm	50Ohm	
Input/Output VSWR	1.4:1 / 1.3:1	
Noise Power Density, dBm/Hz	-68 in Transmit Band, -140 in Receive Band	
Spurious Emission dBc; Non-signal related / Signal related (at Plin)	-60 / -55 max	
AM/PM conversion at Plinear, °/dB	1.0 maximum	
Group Delay	Ripple 1 nsec p-p max over any 40MHz band	

BUC Parameters	
LO Frequency, MHz	4900MHz
Type of Conversion	Single conversion, non-inverting
External 10MHz	Over IF L Band cable with multiplexing
Phase Noise, dBc/Hz	-70 @ 100Hz; -80 @ 1kHz; -90 @ 10kHz; -95 @ 100kHz; -115 @ 1MHz

Power & Mechanical	
AC Voltage Range	190-265V AC 50-60Hz PFC
Size	61 x 51 x 32 cms
Weight	55KG (120lbs)
Cooling	Forced Air
Operating Temperature / Relative Humidity	-40°C to +55°C / Up to 100% condensing



Interfaces	
IF Input Connector	N-type Female
RF Output Connector	CPR137 Grooved
RF Sample	N-type Female
AC Power In	3 pin MS style
RS485 – Ethernet – SNMPv3	MS3112E14-19S

Part Number	Output Power (W)	Prated (dBm / W)	Plinear (dBm / W)	P Cons at Prated	P Cons at Plin
TPB-CB00610- HMS X*	1200W	61 / 1200	58 / 600	5800W	5200W
TPB-CB00620- HMS X*	1500W	62 / 1500	59 / 800	6100W	5800W

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.

Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.