


# Hawk Series 16x8 Extended L-band Matrix

## for Uplink applications

The 1U Hawk Matrix has capacity for two field replaceable matrix cards – which can be combining (fan-in) or distributive (fan-out) – for uplink and downlink applications. The Hawk can be fitted with any combination of cards depending on application, but is ideally suited for smaller gateways with multiple modems and one or two antennas.

Single or dual 8x8 fan-out or fan-in, and single 8x16 fan-out configurations are also available – please enquire.





RF Parameters		
Routing / Capacity	Combining / 16 x input and 8 x output	
Frequency Range	500 to 2450MHz (Extended L-band)	
Switching Time	< 50ms (From receipt of a command to implementation of path change)	
Input & Output Ports	50Ω SMA (All ports DC blocked)	
Gain Typ., mean across band	0±1 dB	
Gain Flatness	<2150MHz	±1.25 dB
	Full band	±2.00 dB
Any 36MHz	<2150MHz	±0.25 dB
	Full band	±0.50 dB
Input Return Loss	Typ. 18 dB Min. 12 dB	
Output Return Loss	Typ. 18 dB Min. 16 dB	
Isolation Min. between any 2 ports	Input-Input	60 dB
	Output-Output	60 dB
	Input-Output	<2150 MHz 55dB >2150 MHz 50dB
Noise Figure	24 typ. (one input routed to one output)	
1dB GCP Gain compression point, output power	<850MHz	+12 dBm
	<2000MHz	+10 dBm
	>2000MHz	+6 dBm
OIP3, 3rd order intercept point	<1500 MHz	Typ. 28 dBm Min. 25dBm
	>1500 MHz	Typ. 25 dBm Min. 20dBm
Group Delay	<1.0 ns across operational bandwidth	
AC Input / AC Consumption	AC Input: 85-264Vac 50/60Hz, AC Consumption: 150W	
Input RF Power	+20dBm absolute maximum	
System Control & Reliability		
Remote Control & Monitoring	Ethernet via RJ45 with HTTPS & SNMPv3, 10BaseT/100 Base Tx. ETL TCP/IP, SNMP & Web browser interface. Via parent chassis.	
Local Control	HMI capacitive touch screen, field replaceable	
PSU Redundancy	Dual redundant and alarmed. Diode OR. Hot swappable	
Matrix Card & CPU	Field replaceable	
MTTR	20 minutes (15 minutes to retrieve spare part and 5 mins to replace) Applies to LRUs only and assumed in-house stock	
Physical & Environmental		
Dimensions	1U high x 550mm deep x 19" wide	
Weight/Colour	<10 kg / RAL9003—White (Semi-matte)	
Temperature	Operating: 0 to 45°C / Storage: -20°C to +75°C	
Location / Humidity	Indoor use only / 20 to 90% non-condensing	
Altitude	2,000 feet AMSL (Operational) 8,000 feet AMSL (Storage) Above Mean Sea Level	
Spec. Version	1.0	

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.  
 Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.