


10MHz GENUS StingRay RF over Fibre module


With ultra low phase noise and 10km nominal range.

StingRay 10MHz Transmit and Receive RF Over Fibre Genus Modules to fit Genus 1U chassis.

Module



Chassis





SRY-G1S-TY-163 & SRY-G1S-RY-164 ■

RF Parameters		
Model Numbers	SRY-G1S-TY-163-xxxx	SRY-G1S-RY-164-xxxx
Frequency Range	10 MHz	
Input ports	50Ω SMA, BNC. 75Ω not available.	
Connectors & impedances	50Ω SMA	50Ω BNC
Input return loss (dB)	Typ. 20dB. Min 15 dB	N/A
Output return loss (dB)	N/A	Typ. 16dB. Min 12 dB
Input AGC level Max (dBm)	+12 dBm. Levels total power including noise	
Input AGC level Min (dBm)	0 dBm Min I/P for max O/P	
Output AGC level Max (dBm)	+12 dBm. Levels total power including noise	
Output AGC level Min (dBm)	0. dBm	
Max Input RF Power (dBm)	+16 dBm. Damage level	
Frequency Offset (Hz)	Phase Noise Typ (dBc/Hz)	Phase Noise Max (dBc/Hz)
0.1	-120	-110
1	-132	-120
10	-144	-130
100	-149	-140
1000	-150	-145
10000	-151	-147
100000	-152	-147
1000000	-152	-147
Laser Type	DFB	-
Optical Wavelength	1310 ± 10 nm	1100 to 1650nm. Optimized for 1310nm and 1550 nm
Optical Power output/input	Output: 5.5 ±2 dBm.	0 to 7dBm. Max 10 dBm
Optical Connectors	FC/APC , SC/APC Single mode fibre.	
Gain Setting Modes	Manual Gain Control (MGC) Automatic Gain Control (AGC) Fixed Gain (FG)	
Module Dimensions	19mm x 38mm x 253mm. 0.2kg. Genus 1U series mountable.	
Module Swap	Hot swap	
Spec Version	1.0	

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.
Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.

