



1PPS to 1MPPS, and IRIG-B (DCLS TTL) GENUS StingRay RF over Fibre module

SRY-G1S-TY-175-xxxx is a low phase noise optical transmit module that converts 1PPS & IRIG DCLS TTL input to 1310nm optical output for timing applications for use in Genus 1U chassis, occupying 1 module slot. It is available with FC/APC or SC/APC optical connectors and RF port options of SMA or BNC in 50 ohm. This unit is designed to work with SRY-G1S-RX-176-xxxx and SRY-G2S-RY-324-xxxxxx for links up to 10km.

Module



Chassis



RF Parameters		
Model Numbers	SRY-G1S-TY-175-xxxxxx	
Input Signal	1PPS to 1MPPS and IRIG DCLS (50 Ohm TTL)	
Input port	50Ω SMA, BNC.	
Input level	5V peak nominal (TTL)	
Duty cycle	0 to 100%	
Rise/Fall Time	<20ns (Measured between 10% low and 90% high thresholds.)	
Jitter	<200ps RMS	
Optical Parameters		
Optical Wavelength	1310nm (Other wavelengths are available)	
Optical power output	+6 dBm Typical	
Optical Connectors	SC/APC, FC/APC (Single mode fibre)	
Non-RF Parameters		
Module swap	Hot swap	
Power consumption	< 5W	
MTBF	>200,000 hours	
Environmental conditions		
Operating Temperature	-20 to +55°C	
Storage Temperature	-40 to +85°C	
Location	Indoor use (Outdoor use as part of ETL ODU only)	
Humidity	20 to 90% non-condensing (Relative Humidity)	
Altitude	10,000 feet AMSL	
Control, Monitoring and Alarms		
Control	Local and Remote	Local front panel control. See chassis spec. Remote control via Ethernet. 10/100Base T. TCP/IP, SNMP, web browser
Temperature monitors	Each module monitored (All are independently monitored and reported)	
Monitoring includes	Input TTL Frequency (in each module)	
Physical Dimensions		
Weight / Dimensions	0.2 Kg typical / 19 x 38 x 253 mm (see figure 1)	

Note-1: Typical parameters are guide figures and measured data may deviate from the quoted figures. ETL endeavours to exceed the quoted typical parameters where practically possible.

Note-2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage. For reliable long term operation do not exceed the parameters given in above.

Note-3: The spec table is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.

