

50W-1000W Ku-Band Rack Mount GaN/GaAs BUC/SSPA

Super High Power Density

The IRT Intelligent Power Block-Up Converter iPB™ Series is smaller, lighter and more powerful allowing significant high-power BUC / SSPA size and weight reduction while substantially improving thermal efficiency, which leads to higher reliability and longer MTBF.

The new IRT 50W-1000W BUC/SSPA iPB™ Series are very compact, light and extremely powerful. Using patent pending Z-combining method and advanced GaN technology, the new IRT 50W - 1000W Rack Mount BUC / SSPA has truly outstanding power density - up to 1000W Psat Ku-Band in 6RU light compact package.

The IRT Rack Mount BUC / SSPA features best in class RF characteristics, RF sample port, true RMS power measurements, extensive monitor and control capabilities enabled via Ethernet, Serial and/or Analog Interfaces. Redundant truly hot swappable power supply gives even higher overall reliability.

Options

- Internal 10 MHz Reference clock
- Autosense 10 MHz Reference clock
- Automated Level Control (ALC) Option
- SSPA option available

Features

- Extremely high power density - up to 1000W PSAT Ku-Band in 19" Rackmount, 6RU
- Superior RF performance
 - Superior Phase Noise: 5-8 dB better than IESS308/309 recommendation
 - Highest Linearity at small back off
 - Wide dynamic range of Gain Control
- RF Overdrive Protection
- Built In Output Isolator – full output VSWR Protection
- RF Sample port
- Redundancy ready with no need of external controller
- True RMS forward and reflected power monitors
- User friendly front panel display and control buttons
- SNMPv3
- Field upgradable SW
- Analogue Interface





50W-1000W Ku-Band Indoor SSPA ■

RF Parameters					
RF Frequency Band, GHz		14 - 14.5GHz / 13.75 - 14.5GHz			
IF Frequency Range, MHz		950 - 1700MHz			
LO Frequency		Single Conversion; non-inverting			
Conversion Gain, dB		75dB min, 77dB typ			
Gain Flatness, dB	Over full band	+/-1 typical , +/-1.5 max			
	Over any 40MHz	+/-0.5 max			
Gain Stability, dB		+/-1.0dB over full temperature range			
Gain Control, dB		20dB minimal dynamic range			
Linearity at Pout=Plin:	2 tone IMD	-24dBc at P linear			
	Spectral Re-growth	-30dBc for QPSK at 1.5xsymbol rate at Plinear			
Noise Power Density, dBm/Hz		-68dBc/Hz @ 100Hz; -80dBc/Hz @ 1kHz; -90dBc/Hz @ 10kHz -95dBc/Hz @ 100kHz; -115dBc/Hz @ 1MHz			
Spurious Emission dBc		-60dBc / -65dBc			
Power & Mechanical					
AC Voltage Range		90-265VAC 50-60 Hz Auto-Ranging; PFC			
Cooling		Forced Air			
Operating Temperature / Relative Humidity		0°C .. +50°C / Up to 99% non-condensing			
Interfaces					
IF Input Connector		N - type female			
RF Output Connector		WR75 Grooved			
AC Power In		NEMA Connector rear panel			
M&C Interface-Serial - Ethernet		DSUB Connectors, RJ45 rear panel			
Part Number	Prated (dBm/w)	Plinear (dBm/W)	P Cons at Prated	P Cons at Plin	RU
IPB-KXB0470-RMSX*	47 / 50	44 / 25	300W	260W	2RU
IPB-KXB0500-RMSX*	50 / 100	47 / 50	600W	520W	3RU
IPB-KXB0530-RMSX*	53 / 200	50 / 100	1100W	800W	4RU
IPB-KXB0540-RMSX*	55 / 300	52 / 150	2000W	1700W	5RU
IPB-KXB0560-RMSX*	56 / 400	53 / 200	2300W	2000W	5RU
IPB-KXB0570-RMSX*	57 / 500	54 / 250	2500W	2200W	5RU
IPB-KXB0590-RMSX*	59 / 800	56 / 400	4500W	4000W	6RU
IPB-KXB0600-RMSX*	60 / 1000	57 / 500	4800W	4200W	6RU

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.
 Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.