

600W-1000W Ku-Band Outdoor BUC / SSPA

Super High Power Density

Smaller, lighter and more powerful SSPA Series allows significant high power BUC / SSPB / SSPA while substantially improving thermal efficiency, leading to higher reliability and longer MTBF.

Powered by GaN technology, the 600W to 1000W Ku-Band SSPA Series are very compact, light and extremely powerful. Weighing only 75 lbs at 500W and 125lbs at 1000W output power, this new Ku-band 600W to 1000W product family is the most powerful and feature rich for its size.

Featuring best in class RF characteristics, true RMS power measurements, extensive monitor and control capabilities enabled via Ethernet, Serial and/or Analog Interfaces. The remarkably compact size and high thermal efficiency results in overall system size and cost reduction making it the ideal candidate for mobile and fixed VSAT applications.

Options

- Internal 10MHz Reference clock
- Autosense 10 MHz Reference clock
- Automatic Level Control (ALC)
- Antenna Mounting Kit
- 1:1 and 1:2 Redundancy Kit
- Remote Control Panel



Features

- Extremely High Power Density
- o Lightweight compact package up to 1000W output power
 - Superior RF performance
 - Available in different frequency options
 - o C-Band-Super-ext, Palapa, Insat
 - o Ku-Band – Ext and Stand Ku-Band in one unit; switchable LO
 - Extensive M&C capability
 - o Superior Phase Noise: 8 dB better than IESS308/309 recommendation
 - o Spurious emission below -60 dBc
 - o Wide range Gain Control
 - o Highest Linearity at small back-off
 - RF Overdrive Protection
 - Redundancy ready with no external controller required
 - Status LED
 - Analogue Interface
 - o Serial: RS 232 & RS 485
 - o Ethernet: embedded Web browser (HTTP) & SNMPv3 support
 - Available in GaAs configuration
 - Input and output True RMS power detection
 - Field upgradable software



RF Parameters		
RF Frequency Band, GHz	13.75 - 14.5GHz	
IF Frequency Range, MHz	950 - 1700MHz	
LO Frequency	12.8GHz	
Conversion Gain, dB	75 minimum, 77 typical	
Gain Flatness, dB	Over full band	+/-1 typical , +/-1.5 max
	Over any 40MHz	+/-0.4 max
Gain Stability, dB	+/-1.5 max over full temperature range	
Gain Control, dB	20dB minimal dynamic range	
Linearity at Pout=Plin:	2 tone IMD	-25dBc max
	Spectral Re-growth	-30dBc for QPSK at 1 x symbol rate
Input Impedance, Ohm	50	
Input/Output VSWR	1.4 : 1 / 1.3 : 1	
Noise Power Density, dBm/Hz	-68 in Transmit Band -140 in Receive Band	
Spurious Emission dBc	-60 Non-signal related / -55 Signal related (at Plin) max	
AM/PM conversion at Plinear, °/dB	1.0 maximum	
Group Delay	Ripple 1 nsec p-p max over any 40 MHz band	

BUC Parameters	
LO Frequency, MHz	4900/12.8-13.05 switchable
Type of Conversion	Single conversion, non – inverting
External 10 MHz Frequency	Over IF L band cable with multiplexing
Phase Noise, dBc/Hz	-70 @ 100Hz; -80 @ 1kHz; -90 @ 10kHz; -95 @ 100kHz: -115 @ 1MHz

Power & Mechanical	
AC Voltage Range	190-265VAC 50-60Hz; PFC
Cooling	Forced Air
Operating Temperature / Relative Humidity	-40°C to +55°C / Up to 100% condensing



Interfaces	
IF Input Connector	N-type Female
RF Output Connector	CPR137 / WR75 Grooved
RF Sample	N-type Female
AC Power In	3 pin MS style
RS485 – Ethernet – SNMPv3	MS3112E14-19S

Part Number	Prated (dBm/w)	Plinear (dBm/W)	P Cons at Prated	P Cons at Plin	Size	Weight	GaAs/GaN
TPB-KXB0580- HMS X*	58 / 600	55 / 300	4000W	3500W	24" x 20" x 12.75"	114lbs/52kg	GaN
TPB-KXB0590- HMS X*	59 / 800	56 / 400	4200W	3600W	24" x 20" x 12.75"	114lbs/52kg	GaN
TPB-KXB0600- HMS X*	60 / 1000	57 / 500	4600W	3750W	24" x 20" x 12.75"	114lbs/52kg	GaN

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.

Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.