

Piranha Genus Standard LNB DC injector

selectable 13/18V 22kHz, up to 500mA.

LNB DC power inserter module (Bias-T) to fit Genus 1U chassis series. Provides selectable 13VDC/18VDC/22kHz tone to LNBs or similar and RF power in monitoring. Full control and monitoring of the module is possible locally through the parent chassis HMI (if fitted), or remotely via Ethernet.

DC Inserter Module



DC Inserter Module

Compact form factor allowing multiple modules to be housed in the Genus chassis. Each module occupies 1 slot in the chassis.

Variable voltage
selectable 13/18VDC, and 22 kHz tone to LNBs.

Hot Swap & replaceable
RF DC Inserter module

Chassis Options

Local control & monitoring
via HMI high resolution touchscreen

Resilience
from dual redundant hot-swap power supplies & field replaceable CPU & HMI

Compact indoor & outdoor
chassis options, which can be part populated

Secure protocols
with SNMPv3 and HTTPS

Flexible Module Configurations
choose from a mixture of DC inserter modules.

Remote control & monitoring
via RJ45 Ethernet port with SNMP & web browser interface

Field replaceable Internal 10MHz reference source
and external reference inject port with auto detection (optional)



Indoor Chassis



Outdoor Unit



PRN DC Power Inserter Module - RF Parameters				
Model Numbers		PRN-G1S-LS2-102		
Size		1 slot wide		
Capacity		Single path		
Frequency Range		850-2450 MHz		
RF Connectors		50Ω SMA	50Ω BNC	75Ω BNC 75Ω F-type
Insertion Loss (dB)		<1.5dB across full band		
Flatness (dB)	Full band	±0.40 dB		
	Any 36MHz	±0.15 dB		
Return Loss (dB)	Typ.	17 dB		
	Min.	14 dB		
Isolation		80 dB min between any two modules		
LNB Voltage		Off. 13V. 18V. 22kHz Tone on/off At port 1. Tolerance ±5% typ.		
LNB Load		Up to 500mA Maximum. Overcurrent protection: Current limited trip and restart.		
Input RF Power		+15dBm. Absolute total maximum		
Module DC Power		12 VDC. Dual redundant 12V bus, module hot swappable		
DC Consumption		12W Full Load. 2W No Load. Max consumption at a steady state.		
RF Power Detect		Range -50dBm to -10dBm total power across band. For indication only		
User Alarms		Via Chassis Ethernet/HMI/Web Interface (upper and lower limits user settable) LNB Current RF Power In		
Module Weight		0.18kg		
Module Dimensions		175mm x 45mm x 20mm maximum. PRN-G1x chassis or Genus 1U series mountable.		
Module Finish		Machined Aluminium		
MTBF		>250,000 hours		
Spec Version		1.0		

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.

Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.

Note 3: All specs are for 50 Ohm connectors unless detailed otherwise.