

5-Channel L- to V-Band Block Upconverter ODU

With triple stage conversion. Housed in an IP65 rated outdoor unit.



RF Parameters (1/2)

| | |
|------------------------|--|
| Capacity | 5 L-band channels IN V-band OUT (Configuration options available for 1 to 5 L-band channels) |
| Input Ports | Five 50Ω SMA or N-type (L-band channels, DC blocked) |
| Output Port | Single Waveguide: UG383 – WR19 |
| Input Frequency Range | Channel 1: 1150 – 2150 MHz Channel 2: 1150 – 2150 MHz Channel 3: 1150 – 2150 MHz Channel 4: 1150 – 2150 MHz Channel 5: 1150 – 2150 MHz |
| Output Frequency Range | Channel 1: 47200 – 48200 MHz Channel 2: 48200 – 49200 MHz Channel 3: 49200 – 50200 MHz Channel 4: 50400 – 51400 MHz Channel 5: 51400 – 52400 MHz |



| RF Parameters (2/2) | | |
|---|--|------------|
| Mean Conversion Gain | Max. 30 ± 2 dB Min. 0 ± 2 dB | |
| Gain Steps | 0.25 ± 0.15 dB | |
| Gain Flatness | Full Band over 5GHz: ± 2.0 dB Over Each 1 GHz Channel: ± 1.5 dB Any 40 MHz in a Channel: ± 0.60 dB | |
| Input Return Loss | Typ. -18 dB Max. -14 dB | |
| Output Return Loss | Typ. -12 dB Max. -10 dB | |
| Noise Figure (at max gain) | Typ. 12 dB Max. 14 dB | |
| Operational Input Level | -75 to -30 dBm | |
| OP1dB (at max gain) | Typ. 6 dBm Min. 3 dBm | |
| OIP3 (at max gain) | Typ. 16 dBm Min. 13 dBm | |
| Group Delay (max pk-pk/1000MHz) | <5.5 ns | |
| Internal Reference Stability | ± 5 x 10 ⁻⁸ (Over -20 to 60°C) | |
| Phase Noise (Typical values when supplied with a high quality external reference and measured at 0 dBm output) | @ 10Hz Offset | -40 dBc/Hz |
| | @ 100Hz Offset | -60 dBc/Hz |
| | @ 1kHz Offset | -80 dBc/Hz |
| | @ 10kHz Offset | -85 dBc/Hz |
| | @ 100kHz Offset | -90 dBc/Hz |
| | @ 1MHz Offset | -95 dBc/Hz |
| Spurs In-band (At -5 dBm output) | Carrier Related (> 1MHz offset) | < -60 dBc |
| | Non-carrier Related | < -75 dBm |
| Spurs Out-of-band (At -5 dBm output) | Carrier Related | < -50 dBc |
| | Non-carrier Related | < -65 dBm |
| Image Rejection | Typ. > 60 dB | |
| LO Breakthrough | Max. -65 dBm | |
| Number of Conversion Stages | Triple | |
| External Reference Input Freq | 10/100 MHz (Auto detection) | |
| External Ref Input Level | +0 dBm ± 5 dB | |
| Spectral Inversion | Non-inverting | |
| Mute | 60 dB | |
| Isolation | 50 dB (Min. between any two L band channels in.) | |



| System Control & Monitoring | |
|-----------------------------|---|
| RF Redundancy | Supported - Option for two units can be paired with redundancy switches to offer RF redundancy system |
| User Alarms | PSUs |
| Remote Control & Monitoring | Ethernet via RJ45, 10BaseT/100BaseTx ETL TCP/IP protocol SNMP v3 Built-in Web Server (HTTPS) |
| Local Control & monitoring | No local control, power and summary alarm status LEDs on connector face. |
| LNB Power | None. |

| Physical & Environmental | |
|--------------------------|---|
| Dimensions | 450mm x 450mm x 200mm maximum |
| Weight | 15Kg |
| Unit Finish | RAL9003 (Signal White) Clear chemical conversion coating to MIL-DTL-5541F Typell Class 3 |
| Temperature | Operating: -20°C to 60°C / Storage: -30°C to +75°C |
| Location | Outdoor / Indoor - IP65 (Appropriate mating connectors used) |
| Humidity | 20 to 90% non-condensing |
| Altitude | 10,000ft AMSL (Operational) 30,000ft/10000m AMSL (Transport) |
| Spec. Version | 0.2 |

Note 1: Typical parameters are guide figures and measured data may deviate from the quoted figures. ETL endeavours to exceed the quoted typical parameters where practically possible.

Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.

Note 3: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.