

Molex Cable Assemblies

Features

RF Components

- Designed for use with our Active RF Components purchased with a Molex connector option e.g., TEEL1-4002-N5N5/1
 (otherwise sold with standard DC filter connector for the DC output) (Active RF components purchased with the Molex
 connector option will be supplied with a Male 3 pin Molex connector.)
- 1 meter or 2 meter length 16/0.2 wire
- Male or Female Molex connector

For use in conjunction with ETL Power supplies with a Molex connector option (denoted by an ML2 suffix e.g., PSU12F125-9701

Molex Cable Assemblies available			
Model Number	Description		
CABMLX-1500-M	1M Length of 16/0.2 wire with 3-pin Male Molex connector.		
CABMLX-1500-F	1M Length of 16/0.2 wire with 3-pin Female Molex connector.		
CABMLX-1501-M	2M Length of 16/0.2 wire with 3-pin Male Molex connector.		
CABMLX-1501-F	2M Length of 16/0.2 wire with 3-pin Female Molex connector.		

PSU Range available				
Model Number	Input	Output	Connector	
PSU12F125-9701-ML2	100-240V (AC), 0.6A	12V (DC), 1.25A	Female 3 pin Molex socket	
PSU18F500-971001-ML2	90-264V (AC), 1.2A max	18V (DC), 5A max	Female 3 pin Molex socket	

CABMLX-1500 Male cable assembly





Marine Oil & Gas





V 2.0 E&OE www.etlsystems.com