

Model Number: D0108S1ULA-22452-xxxx





www.etlsystems.com



Model Number: D0108S1ULA-22452

8-way Single L-band Active Dextra Series Splitter with 10MHz Pass

Technical specifications and operating parameters

		RF	Parameter	rs		
Capacity		8-way				
Frequency Range		850-2450 MHz (Extended L-band)				
Front Panel Monitor		50Ω SMA		-20 dB, 16 dB return loss		
RF Connectors		50Ω SMA	50Ω N-type	50Ω BNC	75Ω BNC	75Ω F-type
Gain		0±1.0 dB Mean across band				
Gain Flatness	Full Band	±0.8 dB	±0.8 dB	±0.8 dB	±1.0 dB	±1.0 dB
	Any 36 MHz	±0.25 dB	±0.25 dB	±0.25 dB	±0.3 dB	±0.3 dB
Input	Typical	20 dB	20 dB	20 dB	20 dB	20 dB
Return Loss	Minimum	16 dB	16 dB	16 dB	16 dB	16 dB
Output Return Loss	Typical	21 dB	21 dB	21 dB	21 dB	21 dB
	Minimum	16 dB	16 dB	16 dB	16 dB	16 dB
Isolation 850-2250 MHz	Typical	28 dB	28 dB	28 dB	28 dB	28 dB
	Minimum	24 dB	24 dB	24 dB	24 dB	24 dB
Isolation	Typical	28 dB	28 dB	28 dB	24 dB	24 dB
2250-2450 MHz	Minimum	24 dB	24 dB	24 dB	22 dB	22 dB
Group	Full Band	2 ns maximum				
Delay Variation	Any 36 MHz	1 ns maximum				
Amplification		Single path amplifier				
Options		Dual redundant amplifier Selectable hot or cold standby, 1:1 redundancy with auto switch-over based on amplifier current monitoring.				
		DC pass port 1 to common port			OPT-D	
		Dual redundant amplifier and DC pass port			OPT-RD	
10 MHz Inse	10 MHz Insertion Loss		<1 dB Port 1 to common only		ý	
Noise	50Ω	10 dB typical				
Figure	75Ω	12 dB typical				
Output 1 dB GCP		0 dBm				
OIP3		+10 dBm				
OIP2		+30 dBm				
3rd Order Intermodulation Level		-40 dBc		With 2 equi-magnitude -13 dBm carriers. Total power -10 dBm		
Input RF Power		16 dBm Absolute maximum				
In Band Spu	In Band Spurious		< -80 dBm			

Environmental			
Operating temperature	0 to 50 °C		
Location	Indoor use only		
Storage temperature	-20 °C to +75 °C		
Humidity	85% non-condensing		
Altitude	10,000 feet AMSL		

Power					
PSU Power	85-264 Vac 50-60 Hz	Fused 2A			
AC Consumption	<20 W	Max. consumption at steady state with max rated LNB current supplied			
LNB Power	current protected at 800 22kHz tone on/off enabl	ed/disabled through comms. tatus available through comms.			
PSU	Dual redundant with dual IEC inlets	Diode OR. Not hot swap			
Hot-swap PSU	No				

System Control				
Monitoring & Remote Control	Redundant amplifiers, LNB current and power supplies monitored via RJ45 port with 10baseT/100baseTX Ethernet offering web browser access, SNMP and ETL proprietary TCP protocol			
Alarms	Dry contact, change-over via 9-way D-type. Available alarms are: PSU and LNB supply. Full status and alarms are also available via the Ethernet interface.			
Display	Tri colour LEDs to indicate PSU, LNB supply and amplifier status.			

Physical			
Dimensions	1U high x 350mm deep x 19" wide		
Weight	3.05 kg		
Colour	RAL9003 - White(Semi-Matte)		

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy. Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.

ETL SYSTEMS LIMITED Coldwell Radio Station Madley Hereford England HR2 9NE TELEPHONE +44 (0)1981 259020

EMAIL info@etlsystems.com

FACSIMILE +44 (0)1981 259021

WEB www.etlsystems.com





