


F-BPL1-7089-xxxx

L-Band Bandpass Filter Passband 950 – 1700 MHz

- Available with RF connectors:
- SMA Female 50Ω
- N-Type Female 50Ω

Physical Dimensions ±0.3mm



General Specification		
Input & Output Connectors	SMA Female 50Ω	N-Type Female 50 Ω
Pass Band Frequency	950 - 1700 MHz	
Center Frequency	1325 MHz	
Insertion Loss	1.0 dB max.	
VSWR	1.7:1 max.	1.6:1 max.
Rejection	≥40dB@DC-840MHz, ≥40dB@1810-2400MHz	
Power Handling	5W CW max	
Operating Temperature	-40°C to +70°C	
Storage Temperature	-55°C to +85°C	
Humidity	95%RH at 40°C	
Shock	20G for 11msec half sine wave,3 axis both direc- tions	
Material and Surface Finish	Aluminium and White Painted	

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy. Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage. Note 3: All specs are for 50 Ohm connectors unless detailed otherwise.

ETL SYSTEMS LIMITED Coldwell Radio Station Madley Hereford England HR2 9NE



EMAIL info@etlsystems.com

WEB www.etlsystems.com

+44 (0)1981 259021

FACSIMILE





www.etlsystems.com

V 1.3 E&OE