



Falcon Series Frequency Converter Module Ka-band to L-Band Block Downconverter

Typical applications:

- Teleports & Earth Stations
- Satellite Operations
- Government & Defence applications
- Telemetry, Tracking & Command
- High Resilience applications

Downconverting Ka-band to L-band. The 1U chassis has the capacity for up to four hot-swap frequency converter modules. These can be all upconverters, all downconverters or a mix of both.

Resilience from dual redundant hot-swap power supplies & field replaceable CPU & HMI

Local control & monitoring via HMI high resolution touchscreen

Compact housed in a 1U high chassis with capacity for up to four modules

Flexible Module Configurations choose from a mixture of up and down converters with different operating frequencies.

Hot Swap & replaceable RF Frequency Converter modules

Redundancy configurations Field-replaceable 2+1 or 1+1 redundant configuration

Field replaceable Internal 10MHz reference source and external reference inject port with auto detection

Secure protocols with SNMPv3 and HTTPS

Remote control & monitoring via RJ45 Ethernet port with SNMP & web browser interface

Chassis - Specification

Dimensions / Weight / Colour	1U high x 550mm deep x 19" wide / <10 kg / RAL9003—White (Semi-matte)
Capacity	Total of 17 module slots. Note that 1 slot will be used for fan (if required) and 1 slot will be used for 10 MHz EXT inject module.
Temperature	Operating: 0 to 45°C / Storage: -20°C to +75°C
Location / Humidity / Altitude	Indoor use only / 20 to 90% non-condensing / 10,000 feet AMSL (Operational) 30,000 feet AMSL (Storage) Above Mean Sea Level
Control & Monitoring	Local: HMI touch screen Remote: Ethernet via RJ45, 10BaseT/100 BaseTx. TCP/IP, SNMP V3 & HTTPS & Web browser interface HMI and CPU field replaceable.
MTTR	20 minutes (15 minutes to retrieve spare part and 5 mins to replace) Applies to LRUs only and assumed in house stock
AC Input / Consumption	85-264Vac 50/60Hz / 150W
PSU Redundancy	Dual redundant and alarmed Diode OR. Hot swappable
Input & Output ports	Dependant upon module fitted





ETL Systems

Excelling in RF Engineering

Model Number:
FN-D-KXL1-24122-K5XX



Frequency Converter Module
Compact form factor allowing multiple modules to be housed in 1U chassis. Each module uses 4 slots in the chassis.

Frequency Downconverter Module - RF Parameters		Redundancy Module - RF Parameters	
Model Numbers	FN-D-KXL1-24122-K5XX	SWF-G1S-QX-108	SWF-G1S-QX-116
Size	4 Slots wide	4 slots wide	4 slots wide
Redundancy	Standalone Module	1+1 (Note. This column denotes specs for 24122 in 1+1 configuration)	2+1 (Note. This column denotes specs for 24122 in 2+1 configuration)
Input Frequency Range	18.8 – 20.0 GHz		
Output Frequency Range	950 - 2150 MHz		
Fixed LO	17 850 MHz		
Conversion Gain	Max 35 ± 2.0 dB Min 5 ± 2.0 dB	Max 28.7 ± 2.0 dB Min -1.3 ± 2.0 dB	Max 27.7 ± 2.0 dB Min -2.3 ± 2.0 dB
Gain Step Size	0.25 ± 0.15 dB		
Gain Flatness (50 Ohm)	Full IF Band Any 40 MHz	±2.0 dB ±0.3 dB	
Input Return Loss (50 Ohm)	Typ. -14 dB / Min. -10 dB	Typ. -11 dB / Min. -7 dB	Typ. -11.0 dB / Min. -7.0 dB
Output Return Loss (50 Ohm)	Typ. -18dB / Min. -14 dB	Typ. -15 dB / Min. -12 dB	Typ. -15 dB / Min. -12 dB
Noise Figure	Typ. 12 dB / Max 15 dB	Typ. 16 dB / Max 19 dB	Typ. 16.5 / Max 19.5 dB
Input Power Range	-75 to -35 dBm		
OP1dB	Typ. +15 dBm / Min. +12 dBm	Typ. 12.2 dBm / Min. 9.2 dBm	Typ. 11.7 dBm / Min. 8.7 dBm
OIP3	Typ. +25 dBm / Min. +22 dBm	Typ. 22.7 dBm / Min. 19.7 dBm	Typ. 22.2 dBm / Min. 19.2 dBm
Internal Reference Stability	± 5 x 10 ⁻⁸ over 0 to 50°C		
Phase Noise (Typical values)	@10Hz offset	-60 dBc / Hz	
	@100Hz offset	-70 dBc / Hz	
	@1KHz offset	-80 dBc / Hz	
	@10KHz offset	-80 dBc / Hz	
	@100KHz offset	-85 dBc / Hz	
	@1MHz offset	-105 dBc / Hz	
Spurs In-band	Non-carrier related	< -75 dBm	
Spurs Out-of-band	Carrier related	< -50 dBc	
	Non-carrier related	< -80 dBm	
LO Breakthrough	< -80 dBm		
Image Rejection	> 50 dB		
External Reference	Input Freq. 10MHz Input Level +3 dBm ± 3dB		
Mute	60 dB		
Number of conversion stages	Single		
Spectral Inversion	Non-inverting		
Spec version	0.4	0.2	0.2

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.
 Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.
 Note 3: All specs are for 50 Ohm connectors unless detailed otherwise.

ETL SYSTEMS LIMITED
Coldwell Radio Station
Madley
Hereford
England HR2 9NE

TELEPHONE
+44 (0)1981 259020

EMAIL
info@etlsystems.com

FACSIMILE
+44 (0)1981 259021

WEB
www.etlsystems.com

