

## Molex Cable Assemblies

ETL Molex cable assemblies are designed for use with our products purchased with a Molex connector option.

Available cable assemblies will include 1 meter & 2 meter length of 16/0.2 wire with a Male or Female Molex connector depending on your purchase.

### Male Cable Assemblies:

Male cable assemblies are intended for use in conjunction with ETL Power supplies with a Molex connector option (denoted by an ML2 suffix ). ETL Power supplies with the Molex option are supplied with a Female connector.

### PSU range available

Model Number	Input	Output	Other
PSU12F125-9701-ML2	100-240V (AC), 0.6A	12V (DC), 1.25A	Female 3 pin Molex socket
PSU120V02-9702-ML2	100-240V (AC), 1.2A	12V to 24V(DC) 5A	Female 3 pin Molex socket
PSU48F150-9703-ML2	100-240V (AC), 2.5A	48V (DC), 3.13A	Female 3 pin Molex socket

**CABMLX-1500-M** - 1M Length of 16/0.2 wire with 3-pin Male Molex connector.

**CABMLX-1501-M** - 2M Length of 16/0.2 wire with 3-pin Male Molex connector.

CABMLX-1500 Male cable assembly



## Photo and physical dimensions

### ETL Active RF Components

All ETL Active RF components come with standard DC filter con for the DC output . ETL Active RF components purchased with the Molex connector option will be supplied with a Male 3 pin Molex connector.

**CABMLX-1500-F** - 1M Length of 16/0.2 wire with 3-pin Female Molex connector.

**CABMLX-1501-F** - 2M Length of 16/0.2 wire with 3-pin Female Molex connector.



CABMLX-1500 Female  
cable assembly



ETL Bias TEE Model TEEL1-  
4002-N5N5/1 (Molex  
option)