



Model Number: 22192-B7B7

Hybrid 8-way IF Active Splitter & Combiner



This hybrid unit comprises of an 8-way IF active splitter and an 8-way IF active combiner accommodated in a 2U high, 19" rack mountable chassis.

Front View of Model 22192-B7B7

The unit benefits from dual redundant power supplies, which can be monitored via the front panel status LED's or via a dry contact alarm port on the rear panel.



Rear View of Model 22192 with 50 ohm BNC connectors

This particular unit has 75 ohm BNC RF connectors but other impedances and connector types are available (model numbers will vary).

















Model Number: 22192-B7B7

RF Engineering and Custom Build

Hybrid 8-way IF Active Splitter & Combiner

Technical specifications and operating parameters

RF Parameters				
SPLITTER				
Capacity		8-way		
Frequency Range		20-200 MHz (IF)		
Gain		1 dB ± 1 dB		
Flatness	Over 20- 200MHz	± 0.5 dB		
	Any 36MHz	± 0.3 dB		
Gain Comp	pression	0 dBm		
Noise Figure	e	7 dB		
Input Return	n Loss	12 dB typical		
Output Return Loss		12 dB typical		
COMBINER				
Capacity		8-way		
Frequency Range		20-200 MHz (IF)		
Gain		1 dB ± 1 dB		
Amplitude Variations	Over 20- 200MHz	± 0.4 dB		
	Any 36MHz	± 0.25 dB		
Gain Comp	pression	+ 10 dBm		
Noise Figure		17 dB		
Input Return Loss		12 dB typical		
Output Return Loss		12 dB typical		

System Control		
Display	Front Panel LED's for Power & PSU status	
Alarms	Dry contact alarm port on rear panel	

Environmental		
Operating temperature	0 to 45°C	
Location	Indoor use only	
Storage temperature	-20°C to +75°C	
Humidity	85% non-condensing	

Physical		
Input Connector	BNC	
Input Impedance	75Ω	
Output Connector	BNC	
Output Impedance	75Ω	
Dimensions	2U high x 350mm deep x 19" wide	
Weight	8 kg	
Colour	White 00-E-55 semi-gloss	

Power		
AC Power	None	
LNB Power	85-264Vac 50/60Hz	
PSU	Dual redundant	
Hot-swap PSU	No	

Key Features
Hybrid unit containing 1 x 8-way Splitter & 1 x 8-way
Dual redundant power supplies
LED's on front panel to indicate PSU status
Dry contact alarm port on rear panel for external power

ETL SYSTEMS LIMITED Coldwell Radio Station Madley Hereford England HR2 9NE TELEPHONE +44 (0)1981 259020

EMAIL info@etlsystems.com

FACSIMILE +44 (0)1981 259021

www.etlsystems.com







