



ETL Systems

New technologies
in RF distribution
www.etsystems.com

Model Number:
HWK-G1S-10

Full model number is dependant upon full matrix module configuration

Hawk Series Dual 8 x 8 Extended L-band Matrix For Uplink & Downlink applications

Typical applications:

- Small Ka/HTS gateway terminals
- LEO gateways
- Oil & Gas
- Deployable VSAT terminals

The 1U Hawk Matrix has capacity for two 8x8 field replaceable matrix cards – which can be the combining or distributive for uplink and downlink applications. The Hawk can be fitted with any combination of cards depending on application, but is ideally suited for smaller gateways with multiple modems and one or two antennas. Model number is dependant upon full matrix module configuration. Single 8x16 & 16x8 configurations are also available - please enquire.

Resilience from dual redundant hot-swap power supplies

Local control & monitoring via HMI high resolution touchscreen

500 - 2450 MHz operating frequency range for Ka-band & HTS applications

Field serviceable & replaceable RF Matrix modules, CPU & HMI

Flexible Module Configurations providing routing solutions including single or dual 8 x 8 distribution modules, dual 8 x 8 combining modules or a combination of distributive and combining modules

Compact housed in a 1U high chassis

Remote control & monitoring via RJ45 Ethernet port, 10BaseT/100/1000BaseTx with SNMP & web browser interface





ETL Systems

New technologies
in RF distribution
www.etlsystems.com

Model Number:
HWK-G1S-10

Full model number is dependant upon full matrix module configuration.

RF Parameters		
Routing	HWK-10 Distributive	HWK-10 Combining
Frequency Range	500 to 2450 MHz (Extended L-band)	
Capacity	2 Matrix Cards – each 8 x Input and 8 x Output.	
Configurations	2 x Distributive (D88D88) / 2 x Combining (C88C88) / 1 x Distributive & 1 x Combining (D88C88) / Single 8x8 Module (D88 or C88)	
Switching Time	< 50ms (From receipt of a command to implementation of path change)	
Input & Output Ports	50Ω SMA (All ports DC Blocked)	
Gain	0±1 dB typical, mean across band	0±1 dB typical, mean across band
Gain Flatness	±1.5 dB	±1.5 dB
Any 36MHz	±0.25 dB	±0.25 dB
Input Return Loss	Typical: 18 dB, Minimum: 14 dB	Typical: 18 dB, Minimum: 14 dB
Output Return Loss	Typical: 18 dB, Minimum: 14 dB	Typical: 18 dB, Minimum: 14 dB
Isolation Minimum between any 2 ports	Input-Input	60 dB
	Output-Output	60 dB
	Input-Output	55 dB <2150MHz, 50 dB >2150MHz
Noise Figure	16 dB typical, with one input routed to one output	24 dB typical, with one input routed to one output
1dB GCP Gain Compression Point, output power	<850 MHz	+0 dBm
	<1500 MHz	+3 dBm
	>1500 MHz	+5 dBm
OIP3 3rd order intercept point	<1500 MHz	Typical 18 dBm, Minimum 16 dBm
	>1500 MHz	Typical 22 dBm, Minimum 20 dBm
Group Delay	<1.0 ns across operational bandwidth	<1.0 ns across operational bandwidth
AC Input / AC Consumption	AC Input: 85-264Vac 50/60Hz AC Consumption: 150W	
Input RF Power	+20 dBm Absolute Maximum.	
Spec Version	1.1	1.1
System Control & Reliability		
Local Control	HMI capacitive touch screen: Field replaceable	
Remote Control & Monitoring	Ethernet via RJ45, 10BaseT/100 Base Tx. ETL TCP/IP, SNMP & Web browser interface.	
PSU Redundancy	Dual redundant and alarmed. Diode OR. Hot swappable	
Matrix Card	Field replaceable	
CPU	Field replaceable	
MTTR	20 minutes (15 minutes to retrieve spare part and 5 mins to replace) Applies to LRUs only and assumed in house stock	
MTBF	Chassis, Switch Card & CPU (TBC)	
Physical & Environment		
Dimensions	1U high x 550mm deep x 19" wide	
Weight / Colour	<10 kg / RAL9003—White (Semi-matte)	
Temperature	Operating: 0 to 45°C / Storage: -20°C to +75°C	
Location	Indoor use only	
Humidity	20 to 90% non-condensing	
Altitude	2,000m AMSL (Operational) 8,000m AMSL (Storage) Above Mean Sea Level	

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.

Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.

ETL SYSTEMS LIMITED
Coldwell Radio Station
Madley
Hereford
England HR2 9NE

TELEPHONE
+44 (0)1981 259020

EMAIL
info@etlsystems.com

FACSIMILE
+44 (0)1981 259021

WEB
www.etlsystems.com

