

## IRT Super High Power Density 1200-1500W C-Band BUC / SSPA

Smaller, lighter and more powerful, this series allows significant high-power BUC / SSPA size and weight reduction and at the same time substantially improves thermal efficiency, which leads to higher reliability and longer MTBF.

The 1200W-1500W C-Band powered by GaN technology KiloBUC® series are compact, lightweight and extremely powerful. Weighing 55KG at 1.5KW output power, this new C-band product family is the most powerful and feature rich for its size.

This series features best in class RF characteristics, RF sample port, true RMS power measurements, extensive monitor and control capabilities enabled via Ethernet, Serial and/or Analog Interfaces. The remarkably compact size and high thermal efficiency results in overall system size and cost reduction

### Options

- Internal 10MHz Reference clock
- Automatic Level Control (ALC)
- Antenna Mounting Kit
- 1:1 and 1:2 Redundancy Kit
- Remote Control Panel



### Features

- Extremely High Power Density
  - o Up to 1.5KW Psat in 61 x 51 x 32 cms
- Superior RF performance
  - o Superior Phase Noise: 8 dB better than IESS308/309 recommendation
  - o Spurious emission below -60 dBc
  - o Wide range Gain Control
  - o Highest Linearity at small back-off
- RF Overdrive Protection
- Redundancy ready with no external controller required
- Status LED
- Analogue Interface
- Available in different frequency options
  - o Super-extended 5.85-6.725GHz
  - o Palapa 6.425-6.725GHz
  - o Insat 6.725-7.025GHz
- Extensive M&C capability
  - o Serial: RS 232 & RS 485
  - o Ethernet: embedded Web browser (HTTP) & SNMPv3 support
- Input and output True RMS power detection
- Field upgradable software

RF Parameters		
Output Frequency Band, GHz		5.85-6.425GHz (other options available)
Input L Band Frequencies, MHz		950-1525MHz
Conversion Gain, dB		80 minimum
Gain Flatness, dB		+/-1 typical +/-1.5 maximum over full band +/-0.4 maximum over any 40MHz
Gain Stability, dB		+/-1.5 maximum over full temperature range
Gain Control, dB		20dB minimum dynamic range
Linearity at Pout=Plin:	2 tone IMD	-25dBc max
	Spectral Regrowth	-30dBc for QPSK at 1 x symbol rate
Input Impedance, Ohm		500hm
Input/Output VSWR		1.4:1 / 1.3:1
Noise Power Density, dBm/Hz		-68 in Transmit Band, -140 in Receive Band
Spurious Emission dBc; Non-signal related / Signal related (at Plin)		-60 / -55 max
AM/PM conversion at Plinear, °/dB		1.0 maximum
Group Delay		Ripple 1 nsec p-p max over any 40MHz band

BUC Parameters		
LO Frequency, MHz		4900MHz
Type of Conversion		Single conversion, non-inverting
External 10MHz		Over IF L Band cable with multiplexing
Phase Noise, dBc/Hz		-70 @ 100Hz; -80 @ 1kHz; -90 @ 10kHz; -95 @ 100kHz; -115 @ 1MHz

Power & Mechanical		
AC Voltage Range		190-265V AC 50-60Hz PFC
Size		61 x 51 x 32 cms
Weight		55KG (120lbs)
Cooling		Forced Air
Operating Temperature / Relative Humidity		-40°C to +55°C / Up to 100% condensing

Interfaces	
IF Input Connector	N-type Female
RF Output Connector	CPR137 Grooved
RF Sample	N-type Female
AC Power In	3 pin MS style
RS485 – Ethernet – SNMPv3	MS3112E14-19S

Part Number	Output Power (W)	Prated (dBm / W)	Plinear (dBm / W)	P Cons at Prated	P Cons at Plin
STS1200C	1200W	61 / 1200	58 / 600	5800W	5200W
STS1500C	1500W	62 / 1500	59 / 800	6100W	5800W

Specifications are subject to change without notice