

Falcon Series Frequency Converter Module

L-Band to K-Band Block Upconverter

L-Band to K-Band block upconverter module with variable gain and slope.

The 1U chassis has the capacity for up to four hot-swap frequency converter modules. These can be all upconverters, all downconverters or a mix of both.

Frequency Converter Module



Frequency Converter Module

Compact form factor allowing multiple modules to be housed in the Genus chassis. Each module occupies 4 slots in the chassis.

Redundancy Configurations

Field-replaceable 2+1 or 1+1 redundant configuration

Hot Swap & Replaceable

RF Frequency Converter modules

Variable Gain & Slope

For balancing input signals.

Frequency Conversion

Up conversion from L-Band to K-Band.

Chassis Options

Local control & monitoring

via HMI high resolution touchscreen

Resilience

from dual redundant hot-swap power supplies & field replaceable CPU & HMI

Compact indoor & outdoor

chassis options, which can be part populated

Secure protocols

with SNMPv3 and HTTPS

Flexible Module Configurations

choose from a mixture of up and down converters with different operating frequencies.

Remote control & monitoring

via RJ45 Ethernet port with SNMP & web browser interface

Field replaceable Internal reference source

and external reference inject port with auto detection



Indoor Chassis



Outdoor Unit

Frequency Upconverter Module - RF Parameters		
Model Numbers		FN-U-KXL1-24458AB-S5S5
Size		4 slots wide
Redundancy		Standalone module
Input Frequency Range		950-1950 MHz
Output Frequency Range		20200 – 21200 MHz
Mean Conversion Gain		0 ± 2 dB
Gain Flatness (50 Ohm)		Full Instantaneous Band: ±1.75 dB Any 40MHz: ±0.3 dB
Input Return Loss		Typ. -20 dB / Min. -18 dB
Output Return Loss		Typ.-18 dB / Min.-14 dB
Maximum Operational Input Level		-20 dBm
OP1dB		Typ +5 dBm, Min 0 dBm
OIP3		Typ +15 dBm, Min +10 dBm
Internal Reference Stability		± 5 x 10-8 over 0 to 50°C
Phase Noise (Typical Values)	@10 Hz offset	-70 dBc / Hz
	@100 Hz offset	-80 dBc / Hz
	@1 KHz offset	-90 dBc / Hz
	@10 KHz offset	-98 dBc / Hz
	@100 KHz offset	-101 dBc / Hz
	@1 MHz offset	-107 dBc / Hz
	@10 MHz offset	-130 dBc / Hz
Spurs In-band (@ -15 dBm output)	Non-carrier related	<-70 dBm
	Carrier related (>1MHz Offset)	<-55 dBc
Spurs Out-of-band (@ -15 dBm output)	Carrier Related	<-55 dBc
	Non-carrier related	<-70 dBm
LO Breakthrough		< -70 dBm
Image Rejection		>60 dB typ.
External Reference Input Frequency		10MHz or 100MHz (auto detection)
External Reference Input Level		0dBm ± 10dB
Mute		60 dB
Number of conversion stages		Dual
Spectral Inversion		Non-inverting
IF Monitor		Yes. Internal RF detector monitored
Spec version		0.1

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.

Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.

Note 3: All specs are for 50 Ohm connectors unless detailed otherwise.