

SpacePath Ultralinear 750W Ka-Band Antenna Mount HPA

The STA5565P Ka series HPA provides ultra linear, high efficiency performance in a compact, lightweight, rugged, weatherproof, antenna mount enclosure. The advanced packaging and cooling techniques enable the unit to operate in extreme environmental conditions from direct rain to direct sunlight. The amplifiers can be simply deployed anywhere in the world, are user-friendly and incorporate a comprehensive remote control facility as standard, including RS485, RS232 and Ethernet options.

The HPA incorporates a high efficiency multi-collector TWT powered by an advanced power supply built on over 30 years of experience in the design and manufacture of satellite amplifiers.


The company's products have an enviable reputation for performance, robust quality and reliable service. The STA5565P Ka is available with a wide range of options and accessories, backed by worldwide technical support.

Features

- Provides up to 370W of CW Power at the flange
- Advanced cooling design enables operation at +60°C and in direct sunlight
- Weatherproof antenna mount construction allows exposed mounting
- Ethernet/SMP/Webpage GUI interfaces
- Broadband – high efficiency operation
- Wide input voltage range - can operate from mains supplies worldwide
- Redundant control - contains control and drive circuits for 1:1 redundancy
- Stand-alone setting - automatically sequences to transmit mode
- Wide range of accessories including: Controllers, waveguide networks, cable assemblies



Block Diagram



RF Performance		
Frequency range*		Full Bandwidth: 27.0 - 31.0 GHz KA1: 27.5 - 30.0 GHz KA2: 30.0 - 31.0 GHz KA3: 27.0 - 30.0 GHz
Output Power (for load VSWR ≤ 1.5:1)	TWT Power	PEAK 58.76 dBm (750 W) CW 56.50 dBm (450 W)
	HPA Flange Power	PEAK 57.95 dBm (625 W) CW 55.70 dBm (370 W)
Gain		≥ 70 dB
Gain Variation, 500 MHz, $\Delta G_{500\text{MHz}}$		≤ 1.2 dB peak-peak
Gain Variation, 1000 MHz, $\Delta G_{1000\text{MHz}}$		≤ 2.5 dB peak-peak
Slope, ΔG_{SLOPE}		± 0.04 dB/MHz max
Gain Stability vs. Time		± 0.25 dB max / 24hrs @ constant drive and temperature
Gain Stability vs. Temperature		± 1.0 dB max / 24hrs @ constant drive and frequency
Adjustment range, G_{ADJ}		30.0 dB typical
Adjustment step size		0.1 dB
AM/PM		≤ 2.5°/dB No Linearizer up to 7dB OPBO / ≤ 2.0°/dB With Linearizer up to 4dB OPBO
Noise Power Ratio (NPR)		≤ -19 dBc at 53.95 dBm/215W flange output power
Inter-modulations (IMD) 2-tone		≤ -23 dBc at total output power of 54.98 dBm/315W
Spectral Re-growth (SR)		≤ -30 dBc
Noise power	Transmit band	≤ -70 dBW/4 kHz
	Receive band	≤ -150 dBW/4 kHz (≤ 21.2 GHz)
Spurious @ $P_o \leq \text{MLP}$		≤ -60 dBc
Residual AM		≤ -50 dBc, $f < 10\text{kHz}$ ≤ -20(1.5+LOG(frequency KHz))dBc, $f = 10\text{KHz to } 500\text{KHz}$ ≤ -85 dBc >500KHz
Phase Noise		10dB below IESS requirement ≤ -50 dBc max, AC fundamental ≤ -47 dBc max, Sum of all spurs
Group Delay (any 80 MHz)	Linear	0.01 nsec/MHz, max
	Parabolic	0.005 nsec/MHz ² , max
	Ripple	0.5 nsec/Peak-Peak, max
Input VSWR (Return Loss)		≤ 1.3:1 (17.7 dB)
Output VSWR (Return Loss)		≤ 1.3:1 (17.7 dB)
Load VSWR (Full perf.)		≤ 1.5:1 (14.0 dB)
Load VSWR (no damage)		≤ 2.0:1 (9.5 dB)
Harmonic 2 nd & 3 rd		≤ -60 dBc

*Note: Other frequency bands are available including BUC options covering 1GHz, consult ETL Systems for details.
 Peak/output power and frequency range must be selected at time of purchase, as these options are TWT dependent and cannot be changed in the field.

Electrical	
AC Input Voltage	100-240 VAC $\pm$ 10%, single phase 47-63 Hz
Power consumption	P1: 1200 VA typical , 1400 VA maximum P2: 1300 VA typical, 1500 VA maximum
Power factor	0.98 typical 0.96 minimum

Physical	
Dimensions (request outline)	52 cm deep x 25.4 cm width x 29 cm height
Weight	21 kg typical
Cooling	Integral forced-air
RF Input	WR-28 (Optional WR-34)
RF Output	WR-28
RF Sample port	2.9mm SMA Female
AC Input	Amphenol C016 20C003 200 12
Ethernet	RJF71B (IP67 RJ45 Connector)
M&C Connector	PT07E18-32S (MS3114E-18-32S)

Environmental	
Operating temperature	-40°C to +60°C (out of direct sunlight) -40°C to +55°C (direct sunlight)
Storage temperature	-54°C to +71°C
Relative humidity	100% condensing
Altitude	12,000 ft. with standard adiabatic de-rating of 2°C/1000 ft., operating 50,000 ft., non-operating
Shock	15 g peak, 11mSec, 1/2 sine
Vibration	3.2 g rms, 10-500 Hz
Acoustic Noise	65 dBA @ $\geq$ 3 ft. from amplifier

Specifications are subject to change without notice